Global Sealer Technologies

Elephant Armor® DELAY is a retarder additive for use with Elephant Armor® Cementitious products to increase working time.

DIRECTIONS FOR USE:

Dissolve DELAY into mixing water.

Each ounce of Delay per 50lbs of Elephant Armor®, will extend desired set time by approximately 10-15 minutes.

Do not exceed 4 ounces per 50 lbs.

Note: Elephant Armor® Delay extends application time but will make the mix less workable.

www.gstinternational.com

Global Sealer Technologies

Elephant Armor®

Our Family of Elephant Armor® Products

- Fiber reinforced: Superior flexural and tensile strength as thin as 1/4".
- High ductility, allowing the overlay or repair to 'FLEX' without failure.
- Resists de-icing salts, freeze/thaw.

- Superior tensile strain capacity over other cement based products for improved crack resistance.
- Superior bond strength to that of other fiber and acrylic based mortars.

- Ideal as a structural underlayment.
- Prevents the propagation of existing cracks through the surface.
- Highly impermeable and abrasion resistent.

Unparalleled as a stampable overlay.

Elephant Armor® Cure *provides an effective curing membrane that will dry to a clear (non-yellowing) membrane.*

Elephant Armor® Primer *a high solids, acrylic polymer latex bonding agent specifically designed to be used with Elephant Armor® on any concrete or asphalt surface.*

Elephant Armor® Overlay Primer *is a ready to use, rewettable polyvinyl acetate bonding agent, which bonds Elephant Armor® mortars to properly prepared concrete, and between Elephant Armor lifts. It can also be used to bond to wood and EPS foam.*

The World's Most Amazing Cementitious Repair and Overlay Product!