



Global Sealer
Technologies



No-Slip is a micronized polymer (finely ground) Slip Resistant Additive that has been designed specifically for use in GST film forming sealers, which include: all Wet Look Lacquers, Lock 'N Seal and Satin Seal.

No-Slip provides a comfortable walking surface for bare feet and will not dissolve in solvents, absorb oil or expand in water.

- **GST's No-Slip must be applied using a low pressure pump sprayer.**
- **To ensure even application of No-Slip, continuous agitation while spraying is required.**
- **Using a brush or roller will cause uneven distribution of No-Slip additive, resulting in slippery areas.**
- **When applying No-Slip to pool coping, use an overspray paint shield to avoid getting sealer in the pool. Be sure to clean paint shield often to avoid excess sealer/No-Slip contaminating the pool water.**
- **No-Slip cannot be used with penetrating sealers and must be used with film forming sealers.**

This product is made from the finest raw materials available and manufactured to proven formulation under strict quality control for its intended use. However, results obtained with the use of this product under a variety of conditions may depend on circumstances beyond our control.

GST International, Inc. (including the seller thereof) warrants only that its products will be free from defects in materials. GST International, Inc.'s (including the seller thereof) sole obligation, and the purchaser's (including the person using or benefiting from its use) sole and exclusive remedy in the event of a defect covered by the foregoing warranty, shall be, at GST International, Inc.'s discretion, to (a) replace the defective product, or (b) refund to the purchaser the purchase price paid for such defective product. There are no warranties other than the limited express warranty provided above. In no event shall GST International, Inc. (or the seller of its products) be liable for incidental or consequential damages resulting or arising from the use of its products.

www.gstinternational.com



Global Sealer Technologies



Our Family of Products:

For Newly Poured Concrete

Use **ConCure** immediately after new concrete is poured. Allow approximately 28 days for new concrete to cure prior to applying any GST Sealer.



Where Efflorescence, Rust or Cement Scale is Present

Use **Clean Concrete** to remove efflorescence, rust and cement staining.

Where Cleaning is Needed or Efflorescence Remover Has Been Used

Use **Pro-Grade Cleaner** to thoroughly clean, remove oil, grease, dirt and prepare the surface prior to applying any of the GST Sealers.

Use **ProGrade Cleaner** to neutralize pH where **Clean Concrete** was used.



Choose an Invisible or Appearance Enhancing Sealer

To be applied after the surface is clean and dry.

Choose an Appearance Enhancing Sealer:

- Low Sheen Wet Look Lacquer
- High Gloss Wet Look Lacquer
- Lock 'N Seal
- Satin Seal
- Stone Enhance
- Final Coat

Choose an Invisible Sealer:

- Water Block
- Stain Block Elite



Product Characteristics:

Use with:

Product Guide

Product Guide	High Gloss	Low Sheen	Satin	Invisible	Light Enhancement	Heavy Enhancement	Repels Water	Repels Grease and Oil	Resists Stains	Resists Efflorescence	Resists Spalling	Removes Oil, Grime	Removes Rust, Efflorescence	Indoor applications	Outdoor applications	Porous Surfaces	Dense Surfaces	Concrete	Exposed Aggregate	Pavers and Slabs	Concrete Block Walls	Brick Masonry	Natural Stone & Travertine	Manufactured Stone	Synthetic Floors	Tiles
High Gloss Wet Look	✓					✓	✓	✓	✓	✓	✓				✓	✓	✓	✓	✓		✓	✓				
Low Sheen Wet Look		✓	✓			✓	✓	✓	✓	✓	✓				✓	✓	✓	✓	✓		✓	✓				
High Gloss Low VOC	✓					✓	✓	✓	✓	✓	✓				✓	✓	✓	✓	✓		✓	✓				
Low Sheen Low VOC		✓	✓			✓	✓	✓	✓	✓	✓				✓	✓	✓	✓	✓		✓	✓				
Lock n Seal			✓		✓		✓	✓	✓	✓	✓				✓	✓	✓	✓	✓	✓	✓	✓				
Satin Seal			✓		✓		✓	✓	✓	✓	✓				✓	✓	✓	✓	✓	✓	✓	✓	✓			
Final Coat	✓				✓										✓		✓	✓				✓		✓	✓	
Stain Block Elite				✓			✓	✓	✓	✓	✓				✓	✓	✓	✓	✓	✓	✓	✓	✓			
Stone Enhance					✓		✓	✓	✓	✓	✓				✓	✓	✓	✓	✓	✓	✓	✓	✓			
Water Block				✓			✓	✓	✓	✓	✓				✓	✓	✓	✓	✓	✓	✓	✓	✓			
Pro-Grade Cleaner												✓			✓	✓	✓	✓	✓	✓	✓	✓	✓			
Clean Concrete												✓	✓			✓	✓	✓	✓	✓	✓	✓	✓			

All products are available in standard one gallon and five gallon sizes. 55 gallon drums and 275 gallon totes are also available upon request.